

**Prepared For:**  
 Kickapoo Township  
 Daniel Kelch  
 8313 N Garden St.  
 Edwards, IL 61528-9797  
 (309)691 - 1518  
 Reference ID: N/A



### Diamond SPEC™

**Presented By:**  
 CENTRE STATE INT'L.  
 Bill Bloom  
 3313 S.W. WASHINGTON  
 PEORIA IL 61602 -  
 (309)637-8483

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

#### Model Profile

#### 2010 Diamond SPEC™ 7400 SFA 4X2 (SA525)

<b>APPLICATION:</b>	Front Plow No Spreader
<b>MISSION:</b>	Requested GVWR: 33000. Calc. GVWR: 33000 Calc. Start / Grade Ability: 34.40% / 2.85% @ 55 MPH Calc. Geared Speed: 68.6 MPH
<b>FUEL ECONOMY:</b>	8.13 MPG @ 55 MPH
<b>DIMENSION:</b>	Wheelbase: 160.00, CA: 85.00, Axle to Frame: 63.00
<b>ENGINE, DIESEL:</b>	{International MaxxForce DT} 260 HP, 800 lb-ft Torque @ 1400 RPM, 2400 RPM Governed Speed, # 2 Bell Housing
<b>TRANSMISSION, AUTOMATIC:</b>	{Allison 3000_RDS_P} 4th Generation Controls; Close Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW & GCW Max.
<b>CLUTCH:</b>	Omit Item (Clutch & Control)
<b>AXLE, FRONT NON-DRIVING:</b>	{Meritor MFS-14-143A} Wide Track, I-Beam Type, 14,000-lb Capacity
<b>AXLE, REAR, SINGLE:</b>	{Dana Spicer 19060S} Single Reduction, 19,000-lb Capacity, Hypoid Gearing, With 190 Wheel Ends Gear Ratio: 6.50
<b>CAB:</b>	Conventional
<b>TIRE, FRONT:</b>	(2) 12R22.5 G149 RSA/RH (GOODYEAR) 483 rev/mile, load range H, 16 ply
<b>TIRE, REAR:</b>	(4) 11R22.5 G164 RTD M+S (GOODYEAR) 497 rev/mile, load range G, 14 ply
<b>SUSPENSION, RR, SPRING, SINGLE:</b>	Vari-Rate; 23,500-lb Capacity, With 4500 lb Auxiliary Rubber Spring
<b>PAINT:</b>	Cab schematic 100GM Location 1: 9219, Winter White (Std) Chassis schematic N/A